

- Industry 4.0 adopted sub-micron Computerized test indicator with computerized MICS system color Touchscreen
- Patents UA126928, UA99686
- Functions: Go/NoGo, Max/Min, Formula, Timer, Linear correction, Temperature correction, Resolution selecting, Connection status
- Memory manager: 2000 values, Folders system, Statistics mode, Memory data transfer
- Quick reading system (50 value/sec)
- **4 MODES DATA TRANSFER:** WIRELESS to MDS app (Windows, Android, iOS, MacOS); WIRELESS HID, WIRELESS HID+MAC, USB HID
- Calibration certificate included (ISO17025 (Ilac MRA))



Item No	Range		Resol.	Accu- racy	Probe	Measu- ring Force	Cable length	Preset	Go/NoGo	Max/Min	Formula	Timer	Temp comp	Linear corr	Calibr date	FW update	Recharge	Memory	WIRELESS	USB	Color Display			
	mm	inch																				mm	µm	mm
120129018			0,0001	±5	12,8	0,1-0,18	Built-in	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		
120129013	-0.8	-0.03"			35,7		Built-in	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
120129019L	+0.8	+0.03"			12,8		2	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
120129019L10					12,8		10	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•

DIAL TEST INDICATOR

- Top quality dial test indicators
- Contrast black dial face
- 0.01 or 0.002 mm resolution
- Adjustable bezel for zeroing
- Jeweled
- Completing with dovetail stem 6 and 8mm
- Calibration certificate included (ISO17025 (Ilac MRA))



Item No	Range	Reso- lution	Repea- tability	Dial face	Accu- racy	Probe	Measuring Force	Scale Diameter
120131080	0-0.8	0,01	3	40-0-40	±10	12,8	0,1-0,18	32
120131020	0-0.2	0,002	1,5	100-0-100	±6	12,8		40