



Item No	Range						Resolution	Accuracy	Weight	Data output
	Common		Anvil		Stem					
	mm	inch	mm	inch	mm	inch	mm	µm	kg	
149001007	300-1000	12-40"	0-350	0-14"	0-350	0-14"	0,001	±30	15	WIRELESS+USB
149002007	600-2000	24-80"						±45	25	
149003007	1600-3000	63-120"						±65	38	
149004007	2600-4000	103-160"	0-700	0-28"	0-700	0-28"		±85	50	
149005007	3600-5000	143-200"						±110	63	
149006007	4600-6000	183-240"						±135	82	
149008007	5500-8000	216-315"						±160	126	
149010007	7500-10000	300-400"	0-1250	0-50"	0-1250	0-50"		±200	172	

OPTIONAL ACCESORIES



FUNCTIONS

- LIMITS (Go/NoGo)
- PEAK VALUES (MAX/MIN)
- MEMORY, WITH STATISTICS
- TIMER
- FORMULA AX^2+BX+C
- MM/INCH
- PRESET
- CALIBRATION DATE CONTROL
- PIN LOCK

- LINEAR CORRECTION
- TEMPERATURE COMPENSATION
- RECHARGEABLE LI-POL BATTERY
- MAGNETIC CHARGING SOCKET

- WIRELESS** APPS FOR WINDOWS, ANDROID, iOS
DATA TRANSFER TO MDS
- USB** HID DATA TRANSFER DIRECT TO WINDOWS, MacOS, ANDROID, LINUX APP'S