


- Industry 4.0 adopted sub-micron micrometer with computerized MICS system with 2,4" color Touchscreen
- **WIDE RANGE (40mm) with NON-ROTATING SPINDLE**
- **Functions:** Go/NoGo, Max/Min, Formula, Timer, Linear correction, Temperature correction, Resolution selecting, Connection indication
- **Memory manager:** 2000 values, Folders system, Statistics mode, Memory data transfer
- **4 MODES DATA TRANSFER:** WIRELESS to MDS app (Windows, Android, iOS, MacOS); WIRELESS HID, WIRELESS HID+MAC, USB HID
- Top quality Aluminium housing (CNC machined solid block)
- **Calibration** certificate included (ISO17025 (Ilac MRA))

MEASURING HUB
MICROTECH DEVICES CONNECT



WIRELESS TO MDS APP
WIRELESS HID+MAC
USB HID



ON-LINE GRAPHIC MODE


Item No	Range	Resolution	Accuracy	Repeat-ability	Measuring HUB	Graphic	Analog scale	Preset	Go/NoGo	Max/Min	Formula	Timer	Temp comp	Linear corr	Calibr date	Recharge	Memory	WIRELESS	USB	Display
	mm	mm	µm	µm																
110170409	0-40	0,0001	±2	0,5	•	•	•	•	•	•	•	•	•	•	•	•	Folders / 2000	Long range /	USB HID /	Touch 2.4"
110170809	40-80		±3		•	•	•	•	•	•	•	•	•	•	•	•				
110171209	80-120		±3		•	•	•	•	•	•	•	•	•	•	•	•				
110171609	120-160		±4		•	•	•	•	•	•	•	•	•	•	•	•				
110172009	160-200		±4		•	•	•	•	•	•	•	•	•	•	•	•				

NON-ROTATING SUB-MICRON MICROMETER

MEASURING HUB
MICROTECH DEVICES CONNECT



WIRELESS TO MDS APP
WIRELESS HID+MAC
USB HID



DOWNLOAD APP



Item No	Range	Resolution	Accuracy	Repeat-ability	Measuring HUB	Graphic	Analog scale	Preset	Go/NoGo	Max/Min	Formula	Timer	Temp comp	Linear corr	Calibr date	Recharge	Memory	WIRELESS	USB	Display
	mm	inch	mm	µm	µm															
110170259	0-25	0-1"	0,0001	±1.5	0,5	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
110170509	25-50	1-2"		±2	0,5	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•