

- Industry 4.0 adopted sub-micron Pistol grip bore gauge with computerized MICS system with 1,54" color Touchscreen
- Patents UA126928, UA99686
- Functions: Go/NoGo, Max/Min, Formula, Timer, Linear correction, Temperature correction, Resolution selecting, Connection status
- Memory manager: 2000 values, Folders system, Statistics mode, Memory data transfer
- **4 MODES DATA TRANSFER:** WIRELESS to MDS app (Windows, Android, iOS, MacOS); WIRELESS HID, WIRELESS HID+MAC, USB HID
- Calibration certificate included (ISO17025 (Ilac MRA))



Item No	Range		Resol.	Accur.	Setting rings	Max depth	Preset	Go/NoGo	Max/Min	Formula	Timer	Temp comp	Linear corr	Calibr date	Recharge	Memory	WIRELESS	USB	Display	
	mm	inch																		mm
133500810	6-8	0.25-0.32"	0,0001	±3	•	50+100	•	•	•	•	•	•	•	•	•	Folders / 2000 val	Long range / HID	USB HID / Update	Touchscreen 1,54"	
133501010	8-10	0.32-0.4"		±3	•	50+100	•	•	•	•	•	•	•	•	•					•
133501210	10-12	0.4-0.5"		±3	•	50+100	•	•	•	•	•	•	•	•	•					•
133501610	12-16	0.5-0.63"		±3	•	65+150	•	•	•	•	•	•	•	•	•					•
133502010	16-20	0.63-0.8"		±3	•	65+150	•	•	•	•	•	•	•	•	•					•
133502510	20-25	0.8"-1"		±3	•	91+150	•	•	•	•	•	•	•	•	•					•
135303010	25-30	1-1.2"		±3	•	91+150	•	•	•	•	•	•	•	•	•					•
133504010	30-40	1.2-1.6"		±3	•	97+150	•	•	•	•	•	•	•	•	•					•
133505010	40-50	1.6-2"		±4	•	97+150	•	•	•	•	•	•	•	•	•					•
133506310	50-63	2-2.5"		±4	•	112+150	•	•	•	•	•	•	•	•	•					•
133507510	62-75	2.5-3"		±4	•	112+150	•	•	•	•	•	•	•	•	•					•
133508810	75-88	3-3.5"		±4	•	112+150	•	•	•	•	•	•	•	•	•					•
133510010	87-100	3.5-4"		±4	•	112+150	•	•	•	•	•	•	•	•	•					•
133512510	100-125	4-5"		±4	•	130+150	•	•	•	•	•	•	•	•	•					•
133515010	125-150	5-6"		±4	option	130+150	•	•	•	•	•	•	•	•	•					•

SET's

Item No	Range		Measuring heads	Setting rings	Max depth
	mm	inch			
133570612	6-12	0.25-0.5"	3pcs	3pcs	50+100
133571220	12-20	0.5-0.8"	2pcs	1pcs	65+150
133572050	20-50	0.8-2"	4pcs	2pcs	91+150
133575090	50-100	2-4"	4pcs	2pcs	65+150
133579130	6-150	0.25-6"	15pcs	up to 100mm	

OPTIONAL ACCESSORIES

STANDARD MDS app
ACCESSORIES FOR DATA TRANSFER

IoT MDS CONNECT DISPLAY UNIT
USB, WI-FI, RJ-45, RS-485, LoRa OUTPUT

DOWNLOAD APP

