


- Calibration stands for ruler & tape calibration
- High resolution 7" LED microscope
- Patents UA147069, UA151330
- **Functions:** On-line Graphic, Analog scale, Go/NoGo, Max/Min, Formula, Timer, Linear correction, Temperature correction
- **Measuring HUB:** Wireless MICROTECH instrument connection, 2D mode,
- **Memory manager:** 2000 values, Folders system, Statistics mode,
- **WIRELESS** long range data transfer to **Free** MICROTECH SPC app
- **WIRELESS HID & USB HID** data transfer to any Windows, Linux, Android, macOS app like keyboard
- **Calibration** certificate included (ISO17025 (Ilac MRA))



Item No	Range		Reso- lution	Accuracy	LED Micro- scope	Magnetic fixator	Force gauge	Calibra- tion	Preset	Go/NoGo	Max/Min	Formula	Timer	Temp comp	Linear corr	Calibr date	Connect. status	Recharge batt	Memory	Wireless	USB	Color Display		
	mm	inch																					mm	mm
258010003	0-1000	0-40"	0,01	±0,010+L/65	+	+		ruler	•	•	•	•	•	•	•	•	•	•	•	•	•	•	Touchscreen 1,54"	
258020003	0-2000	0-80"		±0,015+L/50	+	+			•	•	•	•	•	•	•	•	•	•	•	•	•	•		•
258030003	0-3000	0-120"		±0,020+L/40	+	+			•	•	•	•	•	•	•	•	•	•	•	•	•	•		•
258030005	0-3000	0-120"		±0,020+L/40	+	+	Digital	ruler & tape	•	•	•	•	•	•	•	•	•	•	•	•	•	•		
258050005	0-5000	0-200"		±0,030+L/40	+	+	50N	tape	•	•	•	•	•	•	•	•	•	•	•	•	•	•		

UNIVERSAL COMPUTERIZED STAND CALIBRATOR

- Universal calibration stands for indicators and bore gauges calibration
- Patents UA99931, UA99688
- **Functions:** Go/NoGo, Max/Min, Formula, Timer, Linear correction, Temperature correction, Resolution selecting, Connection indication
- **Memory manager:** 2000 values, Folders system, Statistics mode, Memory data transfer
- **WIRELESS** long range data transfer to **Free** MICROTECH SPC app for Windows, Android, iOS
- **WIRELESS HID & USB HID** data transfer to any Windows, Linux, Android, macOS app like keyboard
- **Calibration** certificate included (ISO17025 (Ilac MRA))



Item No	Range		Resolution	Micrometer head		Calibration devices	Preset	Go/NoGo	Max/Min	Formula	Timer	Temp comp	Linear corr	Calibr date	Connect. status	Recharge batt	Memory	Wireless	USB	Color Display				
	mm	inch		mm	mm																μm			
25111300	0-300	0-12"	0,0001	25	±2	Bore gauges Indicators	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•			
25111500	0-500	0-20"					•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
25111900	0-1000	0-40"					•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•