

# DIGITAL INDICATOR IP65

- High quality indicator with IP65 proof
- PRESET, mm/inch, HOLD function
- USB data transfer
- CR2032 3V battery
- Calibration certificate included (ISO17025 (Ilac MRA))

Item No	Range		Resolution		Accuracy	Force	Proof	mm/inch	Preset	ABS	USB DATA
	mm	inch	mm	inch	µm	N					
120125131	0-12,7	0-0,5"	0,01	0.0005"	±10	0.6-1	IP65	•	•	•	•
120125132			±6	•	•			•	•		
120125133			0,001	0.00005"	±4			•	•	•	•
120125134			±3	•	•			•	•		
120125135			±2	•	•			•	•		
120125250	0-25,4	0-1"	0,01	0.0005"	±20	0.7-1.2		•	•	•	•
120125251			±10	•	•			•	•		
120125252			0,001	0.00005"	±6			•	•	•	•
120125253	±4	•	•	•	•						
120125500	0-50,8	0-2"	0,01	0.0005"	±20	1.2-2.2		•	•	•	•
120125502			0,001	0.00005"	±7			•	•	•	•
120125503			±5	•	•			•	•		
120125901	0-100	0-4"	0,01	0.0005"	±20	3-5		•	•	•	•
120125902			0,001	0.00005"	±12			•	•	•	•
120125904			±8	•	•			•	•		
120125951			0,01	0.0005"	±30		•	•	•	•	
120125952	0-150	0-6"	0,001	0.00005"	±20	•	•	•	•		
120125954			±10	•	•	•	•	•	•		



### OPTIONAL ACCESSORIES



120125000 USB HID DATA TRANSFER CABLE  
DIRECT DATA TRANSFER, LIKE A KEYBOARD

# DIAL INDICATOR

- Top quality dial indicator
- 0.01 or 0.001mm resolution
- Jeweled bearing
- Modification with SHOCKPROOF & WATERPROOF
- With adjustable tolerance markers
- Calibration certificate included (ISO17025 (Ilac MRA))

Item No	Range	Resolution	Accuracy	Bezel D	Shockproof	Jeweled	Tol. markers	Waterproof	Rubber sleeve
	mm	mm	µm	mm					
120121010	0-1	0,001	±3	60	•	•	•	•	•
120121100	0-10	0,01	±15		•	•	•	•	•
120120100			±25		•	•	•	•	•
120121300	0-30	±35	•		•	•	•	•	
120121500	0-50	±40	•		•	•	•	•	
120121990	0-100	•	•		•	•	•	•	

